

# DOT 4 BRAKE FLUID

## BRAKE FLUID

Product formulated with a polyalkaline mixture of glycol ethers in conjunction with other high performance additives and inhibitors which provide essential system protection against the effects of corrosion and blocking of the system by the formation of bubbles due to high temperatures. It is recommended to change the brake fluid after 2 years of service. Take extreme care to avoid spilling over paint. Complies: UNE 26-109-88, SAE J1704, FMVSS N-116 DOT 4, ISO 4925 Road Vehicles. Boiling point: 265 ° C.

### MODE OF USE

Direct use. Do not use in brake systems for which fluid based on mineral oil is recommended.

### CHARACTERISTICS

Appearance:

Color: Brown

Odor: Characteristic

pH: 8 (10 %)

Eye Irrit. 2: H319 - Causes serious eye irritation.

P264 Wash thoroughly after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

**Chemical description:** Additive/s

Maximum V.O.C. content: 104,94 g/L (20 °C)

### Warning

