www.flowquimica.es info@flowquimica.es +34 91 808 25 29 C/ Dinamismo 3 P.I. Los Olivos 28906 Getafe Madrid, Spain

A-1604RS 18/10/2017



ANTIFREEZER 10% Pink antifreezer refrigerant

Antifreezer & Coolant for direct use, made from glycols and corrosion inhibitors of high technology to provide complete protection to all components of the refrigeration circuit. Excellent corrosion protection for all metals and alloys in the circuit, as well as high cooling and boiling power. Concentration: 10%. Freezing point -6°C. Boiling point 110 °C. Applicable to any car brand.

MODE OF USE

Direct use. Do not dilute.

CHARACTERISTICS			
	APPEARANCE		Transparent
	COLOR		Hot magenta
	ODOR	4	Odourless
	рН		7,5 - 8,5
CHEMICAL DESCRIPTION		Glycol/s	

Skin Sens. 1: H317 - May cause an allergic skin reaction.

P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501 Dispose of the contents/containers in accordance with the current legislation on waste treatment.

Substances that contribute to the classification: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 55965-84-9)

For use in industrial installations or professional treatment onlyMaximum V.O.C. content: 115 g/L (20 °C)

Warning





