



ORGANIC ANTIFREEZE 30%

GREEN ANTIFREEZE REFRIGERANT

A-0603VE

Antifreeze fluid and organic refrigerant for direct use. Glycol base Excellent duration and protection (maintenance free) against corrosion, cavitation, freezing and boiling. High inhibitory power that prevents metal corrosion and cavitation in aluminum cylinder heads, pumps, etc. It does not affect the stability of the joints. Free of phosphates and amines. Suitable for any type of vehicle. Concentration: 30% Max freezing point: -18°C. Boiling point max: +117°C. Exclusive professional use.

Mode of use

Direct use. Do not dilute.

<i>Appearance</i>	Transparent
<i>Color</i>	Green
<i>Odor</i>	Mild
<i>pH</i>	8 - 9
<i>Density</i>	1020 - 1080 kg/m ³
<i>Chemical description</i>	Glycol/s

Warning

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Skin Sens. 1A: H317 - May cause an allergic skin reaction. - P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P501 Dispose of the contents/containers in accordance with the current legislation on waste treatment - Substances that contribute to the classification: METHYLCHLOROISOTHIAZOLINONE / METHYLISOTHIAZOLINONE (CAS 55965-84-9) - For use in industrial installations or professional treatment only Maximum V.O.C. content: 5,36 g/L (20 °C)



UFI: 4PNF-K90Q-D005-DJ6U

04/06/2020