

Balboa Chemical, S.L.
www.flowquimica.es
info@flowquimica.es
+34 91 808 25 29
C/ Dinamismo,3
P.I. Los Olivos
28906 Getafe, Madrid
Spain

FU-06



FÁBRICA DE PRODUCTOS QUÍMICOS
MANUFACTURE OF CHEMICAL PRODUCTS



ANTIFREEZE G.13 CONCENTRATE

100% GREEN ORGANIC PURE CONCENTRATE COOLANT REFRIGERANT

Antifreeze fluid and organic refrigerant. Ethylene glycol base of the highest degree of purity and glycerol. Excellent duration and protection (maintenance free) against corrosion, cavitation, freezing and boiling. Based on the latest OAT (Organic Acids Technology) technology that combines salts of organic acids with a high inhibitory power that prevents metal corrosion and cavitation in aluminum cylinder heads, pumps, etc. It does not affect the stability of the joints. Free of nitrites, phosphates, borates and amines. Suitable for any type of vehicle. Concentration: 100% Max freezing point: -40°C. Boiling point max: + 190°C.

Mode of use

To dilute. Freezing point: -10°C: use at 20%, -16°C: 30%, -23°C: 40%, -35°C: 50%. It does not require manipulation. Do not mix with other organic refrigerants. Not suitable for old copper, brass or lead radiators. Max duration: 5 years, 250,000 km tourism, 650,000 km truck / bus, 32,000 hours stationary engine. Meets standards: ASTM D3306; UNE 26-361-88 / 1; BS 6580; MAN 324 TypeSNF; MB-325.3; VW TL-774D / F (G12 / G12 +); RenaultTrucks41-01-001 / S Type D; Ford WSS-M97B44-D / E; VOLVO AB, etc.

Appearance
Color
Odor
pH
Chemical description

Transparent
Green
Mild
8,1 - 8,5
Glycol/s

Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Skin Sens. 1A: H317 - May cause an allergic skin reaction. - P264 Wash thoroughly after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P501 Dispose of the contents/containers in accordance with the current legislation on waste treatment. - Substances that contribute to the classification: GLYCOL (CAS 107-21-1); METHYLCHLOROISOTHIAZOLINONE / METHYLISOTHIAZOLINONE (CAS 55965-84-9) - For use in industrial installations or professional treatment only Maximum V.O.C. content: 322,01 g/L (20 °C)



02/01/2020

Warning

BALBOA CHEMICAL